



APPLICATIONS

Eni Brake Fluid DOT 4 Plus is a high performance synthetic fluid, especially suitable for those cases where the brake system is subject to severe operating conditions.

CUSTOMER ADVANTAGES

- With its high boiling point, **Eni Brake Fluid DOT 4 Plus** can be safely used in demanding environmental conditions, or prolonged braking actions that overheat the braking system.
- This product has a high resistance to the harmful contamination from external moisture, which causes a drop in the boiling point and the so-called vapour lock (formation of gas bubbles in the circuit, with a consequent lack of braking effects).
- The viscosity characteristics of the product have been adjusted in order to make it suitable for use also at low ambient temperatures.
- **Eni Brake Fluid DOT 4 Plus** is not corrosive to the metals used in brake circuits, and does not swell rubber or plastic components, preventing any damage to seals and gaskets. It also has good lubricant properties with an antiwear action, and is chemically stable even at high temperature.

SPECIFICATIONS AND APPROVA

- FMVSS 116, DOT 4+
- SAE J 1704
- ISO 4925/05 (CLASS 04)





CHARACTERISTICS

Properties	Method	UNIT	Typical
Appearance	-	-	clear
Density at 20°C	ASTM D 1298	kg/m ³	1075
Viscosity at -40°C	ISO 4925/05-5.1	mm ² /s	1300
Water content	ASTM D 1364	%(m/m)	0.07
pH	ISO 4925/05-5.3	-	9.3
Dry boiling point	ISO 4925/05-5.2	°C	295
Wet boiling point	ISO 4925/05-5.2.6	°C	215
Flash point	ISO 4925/05-5.2	°C	148

WARNINGS

- To prevent contamination by atmospheric moisture, which lowers the boiling point of the product, it is strongly recommended that only fluid from sealed containers is used. Keep containers clean and tightly closed. Do not use fluid from cans which have been previously opened and not properly closed.

