



600 DIJET 2T

Biodegradable 2 Stroke engine oil

Jet Ski & PWC - High Performance and Racing

100 % Synthetic - Ester - NMMA TC-W3

TYPE OF USE

Designed for racing, high performance 2 Stroke engines fitted with Direct Injection or carburetors, high performance and racing use.

For Jet Ski, Water Scooter, PWC – Personal Water Craft, Watercraft,... 2 Stroke engines lubricated by premix or by oil injector systems: KAWASAKI, YAMAHA, POLARIS, BRP....

Suitable for all type of Gasoline fuels, leaded or unleaded, with or without Ethanol, biofuels.

PERFORMANCES

PERFORMANCES

NMMA TC-W3 / TC-WII / TC-W

Biodegradability: CEC L-33-A-93 / OECD 301B.

High performance oil without solvent: 100% Synthetic - Ester base stock reduces frictions for higher power output.

Exceeds the NMMA TC-W3 upper standard level, low smoke.

Ashless technology protects the engine against carbon deposits build-ups, spark plug fouling, exhaust port and piston rings blocking.

Environment friendly: vegetal esters bases achieve 82% of biodegradability according to CEC L-33-A-93 standard and 69% according to OECD 301B standard.

Mixes instantaneously with all type of gasoline and remains stable.

RECOMMENDATIONS

Mixing ratio for premix lubrication: from 1% to 2% according to manufacturers' requirements and to be adjusted according to your own use.

PROPERTIES

Color	Visual	Amber
Density at 20°C (68°F)	ASTM D1298	0.932
Viscosity at 40°C (104°F)	ASTM D445	50 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	8.5 mm ² /s
Viscosity index	ASTM D2270	147
Flash point	ASTM D92	258°C / 496°F
Pour point	ASTM D97	-42°C / -44°F
Biodegradability	CEC L-33-A-93	82%
Biodegradability	OECD 301B	69%

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 Aubervilliers Cedex - BP 94 – FRANCE. Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79. Web Site: www.motul.com

01/20