



HYPO SYNT 75W-90

Lubricant for BMW hypoid rear differential

100% Synthetic

TYPE OF USE

Specially formulated for BMW rear axle without limited-slip differential with plates or with viscostatic limited-slip (325i 4WD)

For BMW rear axle with limited-slip differential with plates or with EH limited-slip (525i 4WD), use MOTUL HYPO SYNT LS.

PERFORMANCES

STANDARDS : API GL4 and **GL5** / MIL-L-2105D
PERFORMANCE : BMW

Very high lubricating power which decreases friction and wear
Extreme pressure, Anti-wear, Anti-corrosion, Anti-foam.

RECOMMENDATIONS

Oil change: According to BMW requirements and adjust according to your own use.

PROPERTIES

Viscosity grade	SAE J 306	75W-90
Density at 20°C (68°F)	ASTM D1298	0.858
Viscosity at 40°C (104°F)	ASTM D445	103 mm ² /s
Viscosity at 100°C (212°F)	ASTM D445	15.1 mm ² /s
Viscosity index	ASTM D2270	163
Flash point	ASTM D92	220°C / 428°F
Pour point	ASTM D97	-57°C / -71°F

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty.

MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - TEL : 33 1 48 11 70 00 - FAX : 33 1 48 33 28 79 - Web Site : www.motul.fr

09/10