



Translube Expert 75W-90

Lubricant for Outboard Propeller Box

Technosynthese®

TYPE OF USE

High Performance anti-emulsion gear oil specially formulated to lubricate outboard big engine high loaded propeller boxes:

EVINRUDE, FORCE, JOHNSON, MARIMER, MERCURY, SEAGULL, SELVA, SUZUKI, TOHATSU, YAMAHA,...etc.

Specially developed for outboard big engine propeller boxes operating under shocks, heavy loads and low revolution speed, or moderate loads and high revolution speed.

Suitable also for all transmissions systems using gears, bevel gears, stepdown gears,...etc.

PERFORMANCES

STANDARDS API GL-5 and GL-4
 MIL-L-2105D

Technosynthese® lubricant with "Extreme Pressure" additive for efficient anti-wear protection, better resistance at high temperature and extended life time.

Formula reinforced with synthetic base stocks to increase oil film resistance even in the most extreme conditions.

Very high lubricating properties to reduce friction and wear.

Viscosity grade 90 at high temperature to provide outstanding oil film resistance at high temperature and high load, and to reduce transmission noise.

Anti-corrosion, Anti-foam.

High anti-emulsion properties.

RECOMMENDATIONS

Drain period: according to manufacturers' recommendations and to be adapted to your own use.

A drain once a year is recommended in any case.

Not to be used in electrical reverse gear system.

PROPERTIES

Viscosity grade	SAE J 306	75W-90
Density at 20°C (68°F)	ASTM D1298	0.858
Viscosity at 40°C (104°F)	ASTM D445	114.1 mm²/s
Viscosity at 100°C (212°F)	ASTM D445	17.1 mm²/s
Viscosity Index	ASTM D2270	164
Flash point	ASTM D92	215°C / 419°F
Pour point	ASTM D97	-42°C / -44°F