

DIESEL TURBO UHPD 10W40

AUTOMOTIVE

Lubricants



Description

It is a next-generation synthetic lubricant oil of the highest quality. It is especially recommended for supercharged diesel engines of long-haul commercial vehicles (TIR) with extremely long periods of change. The product is specifically designed for low-emission diesel engines that meet Euro 5 or previous standards, from certain manufacturers that do not include particulate filters. The oil was adopted by Scania for its new generation of Euro 6 engines.

Properties

- It can be used when using biodiesel as fuel, in accordance with the manufacturer-recommended change periods.
- The oil is highly resistant to oxidation, consumes little power and has excellent shear strength, ensuring the high oil change interval required by Scania in their LDF specifications.
- It is a multigrade oil with a high range of temperatures and high cold flow, allowing greater fuel economy than oils with other viscosity levels.
- The trials we carry out allow us to ensure close control of engine cleanliness, exceeding the minimum required by international standards, thus preventing the formation of sludge and deposits in the piston and segments.
- The trials conducted in motors with high EGR rates ensure perfect control of the soot that is characteristic of these exhaust after-treatment systems.
- Compared to other oils with similar characteristics, the specific control of sulphur and phosphorus of its formulation ensures compatibility with oxidation catalysts as well as with current SCRs and those from the next generation of Euro 6 engines.
- The field trials performed to gain Scania LDF-3 approval ensure engine durability in harsh conditions that can be applied to any climate, or with periods of very high oil change.

Quality Levels

- API CF
- MB 228.5
- VOLVO VDS-3
- ACEA E4/E7
- MAN 3277
- SCANIA LDF-3
- RENAULT RLD-2/ RXD
- MACK EO-N
- CUMMINS CES 20072
- DAF EXTENDED DRAIN
- MTU Type 3

A safety information file is available on request.

repsol.com
+34 901 111 999

Technical data sheet for Lubricants. Revision 8. October 2016.

DIESEL TURBO UHPD 10W40

AUTOMOTIVE

Lubricants



Technical specifications

	UNIT	METHOD	VALUE
SAE GRADE			10W40
Density at 15 °C	g/mL	ASTM D 4052	0.865
Viscosity at 100 °C	cSt	ASTM D 445	13.4
Viscosity at 40 °C	cSt	ASTM D 445	86
Viscosity at -25 °C	cP	ASTM D 5293	7000 max.
Viscosity index	-	ASTM D 2270	150 min.
Flash point, open cup	°C	ASTM D 92	215 min.
Pour point	°C	ASTM D 97	-36
T. B. N.	mg KOH/g	ASTM D 2896	16.0
Sulphated ashes		ASTM D 874	1.9
Bosch Injector Shearing: Viscosity at 100 °C after shearing	cSt	ASTM D 3945	12.5 min.

A safety information file is available on request.

repsol.com
+34 901 111 999

Technical data sheet for Lubricants. Revision 8. October 2016.